



Important Notes:



- Check Online vehicle fit guide before use.
- NOT SUITABLE FOR 2 DOOR VEHICLES.
- All items being carried (surfboards, sail boards, kayaks, ladders etc.) require the use of front and rear tie-down straps (not included). Bow and stern safety tie-downs are required for all Malone rooftop transport(s). Failure to correctly install and use safety tie-down lines voids all warranty and liability.
- This product May Not be Suitable for use on vehicles that are fitted with side curtain or overhead airbags. The straps can prohibit the airbags from deploying properly.
- Crossbars must be at least 24" apart for safe transport.
- Do not tamper with load strap and/or buckle while in transit.
- Do Not Use In Rain, water can potentially run down nylon strapping when wet and into vehicle.
- Remove the product before entering a carwash.
- Make sure your vehicle roof is clean from any dust and dirt before installing.
- The VersaRailTM has been designed as a temporary roof load carrying system and should not be left fitted to the vehicle when not in use.
- The VersaRailTM is NOT suitable for use with rooftop tents.

IMPORTANT MOUNTING NOTES ON NEXT PAGE



IMPORTANT NOTE ON MOUNTING:



- **CAREFUL ATTENTION MUST** be made to the placement of the towers on the vehicles roof. This is a very critical step to safety and function.
- The proper placement is right along the edge of the roof, at it's strongest point. The vacuum cups will act as cushions or pads even if placed over roof ridge lines preventing a full seal.
- Do Not place towers inwards or on a glass sunroof.

NOTE TOWER POSITIONS BELOW:



WRONG PLACEMENT



CORRECT PLACEMENT



MALONE AUTO RACKS 81 County Rd. Ste 1, Westbrook, ME 04092

P: 207.774.9100 F: 207.615.0551

E: support@maloneautoracks.com W: www.maloneautoracks.com