

MALONE TRAILER SPECIFICATIONS	<u>MicroSport</u>	<u>MicroSport XT</u>	<u>MicroSport LowBed</u>
WEIGHT (WITHOUT ACCESSORIES)	197 LBS	230 LBS	190 LBS
LENGTH	13' 3"	13' 3"	13' 3"
WIDTH WITH CROSSBARS	78"	78"	78"
WIDTH WITHOUT CROSSBARS	55"	55"	55"
FRAME WIDTH ASSEMBLED	40"	40"	40"
REQUIRED BALL SIZE	2"	2"	2"
BALL HEIGHT FROM GROUND	18"	15"	18"
LOAD CAPACITY	800 LBS (DOUBLE LEAF SPRING)	800 LBS (DOUBLE LEAF SPRING)	800 LBS (DOUBLE LEAF SPRING)
MAXIMUM BOAT LENGTH (CENTERED/NOT CENTERED)	20'/18'	20'/18'	20'/18'
RECOMMENDED TIRE PRESSURE	40 PSI, 90 PSI MAX	40 PSI, 90 PSI MAX	40 PSI, 90 PSI MAX
TIRE SIZE	4.80-12"	4.80-12"	4.80-12"
TIRE SPECIFICATIONS	LOAD RANGE B (785 LBS), 4 P.R. RATED TO 65MPH	LOAD RANGE B (785 LBS), 4 P.R. RATED TO 65MPH	LOAD RANGE B (785 LBS), 4 P.R. RATED TO 65MPH
WHEEL + HUB SPECIFICATIONS	12" WHEEL DIAMETER	12" WHEEL DIAMETER	12" WHEEL DIAMETER
	1.98" HUB I.D.	1.98" HUB I.D.	1.98" HUB I.D.
	5-9/16" STUDDER FLANGE O.D.	5-9/16" STUDDER FLANGE O.D.	5-9/16" STUDDER FLANGE O.D.
	5x4.5" BOLT PATTERN	5x4.5" BOLT PATTERN	5x4.5" BOLT PATTERN
	1/2"-20 STUD THREAD PITCH	1/2"-20 STUD THREAD PITCH	1/2"-20 STUD THREAD PITCH
	1-1/16" AXLE SPINDLE DIAMETER	1-1/16" AXLE SPINDLE DIAMETER	1-1/16" AXLE SPINDLE DIAMETER
TONGUE WEIGHT (UNLOADED)	25 LBS	25 LBS	25 LBS
CROSSBAR SPREAD	44"-63"	44"-63"	44"-63"
HEIGHT OF CROSSBARS FROM GROUND	30"	30"	22" and 58"
FRAME & TONGUE MATERIAL	MARINE GRADE PRE-GALVANIZED 11 GAUGE STEEL	MARINE GRADE PRE-GALVANIZED 11 GAUGE STEEL	MARINE GRADE PRE-GALVANIZED 11 GAUGE STEEL
FRAME CONSTRUCTION	C-CHANNEL 1.5" WIDE x 3.5" HIGH	C-CHANNEL 1.5" WIDE x 3.5" HIGH	C-CHANNEL 1.5" WIDE x 3.5" HIGH
TONGUE CONSTRUCTION	2"x3"x90"	2"x3"x90"	2"x3"x90"
CROSSBAR CONSTRUCTION	1.25" SQUARE PRE-GALVANIZED 14 GAUGE STEEL	1.25" SQUARE PRE-GALVANIZED 14 GAUGE STEEL	1.25" SQUARE PRE-GALVANIZED 14 GAUGE STEEL
LIGHTING	L.E.D. LIGHT KIT WITH CUSTOM PLUG & PLAY WIRING HARNESS	L.E.D. LIGHT KIT WITH CUSTOM PLUG & PLAY WIRING HARNESS	L.E.D. LIGHT KIT WITH CUSTOM PLUG & PLAY WIRING HARNESS
SHIPPING BOX COUNT (BASE TRAILER)	4	5	4